

SE-601 Series six-channel ECG



Technical specifications

Model	SE-601A	SE-601B	SE-601C
Input circuit	Defibrillation protection		
Lead	Standard 12 leads		
Acquisition mode	12 channel simultaneous acquisition (10-24s adjustable)		
A/D converter	24 bits		
Sampling rate	1000Hz/channel, 10,000Hz for pacemaker detection		
Input voltage range	± 5mVp-p		
Time constant	> 3.2s		
Frequency response	0.05Hz-150Hz		
Calibration voltage	1mV ± 2%		
Sensitivity	2.5, 5, 10, 20, 10/5, AGC (mm/mV)		
Input impedance	> 50MΩ		
Input circuit current	< 10nA		
Noise level	< 12.5 μVp-p		
Patient leakage current	< 10 μVp-p (220V-240V)		
Patient auxiliary current	< 0.1 μA (DC)		
Filters	EMG filter 25Hz/35Hz/45Hz/OFF		
	Anti-baseline drift 0.05/0.15/0.25/0.5Hz		
	Low-pass filter 75Hz/100Hz/150Hz		
	AC filter 50Hz/60Hz		
CMRR	> 115 dB		
Recording modes	Auto/manual/rhythm		
Rhythm lead	Single channel or three channels selectable		
	AC (100-240V@50/60Hz)		
Power supply	12V Vehicle-Carried Inverter Li-ion Battery		
Battery	Built-in rechargeable Li-ion battery, 2200mAh@14.8V for 6 hours general use or 280 copies ECGs continuous printing		
Recorder	Thermal printer		
Recording paper	110mm*140mm*144P (Z-fold)		
Recording speed	5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50 mm/s (± 3%)		
Weight	Approximately 3 kg (including battery and paper)		
Dimensions	322mm × 310mm × 101mm		
Display	3.5 inch STN LCD, 192*64 dots	5.7 inch STN LCD, 320*240 dots	5.7 inch TFT color LCD, 640*480 dots
External input	100KΩ, sensitivity 10mm/V ± 5%		
External output	100Ω, sensitivity 1V/mV ± 5%		
Communication interfaces	Ethernet or RS232		

EDAN



SE-601 series six-channel ECG

Six-channel ECG SE-601 series: SE-601A • SE-601B • SE-601C, cost-effective solutions for any working situations including hospital wards, routine check, home visit and emergency cases.



Edan Instruments, Inc.

3F-B, Nanshan Medical Equipments Park, Nanshan Rd 1019#., Shekou, Nanshan, Shenzhen, 518067 P.R. China
Tel: 86-755-2689 8326 Fax: 86-755-2689 8330 www.edan.com.cn Email: info@edan.com.cn



ENG-ECG-SE601 -V1.0-20090305

All rights reserved.
Features and specifications are subject to change without notice

SE-601 series six-channel ECG



Portable and compact design



Alphanumeric keyboard



PC-based data management software
(Smart ECG Viewer)



SE-601C
Large backlight color screen (5.7 inch TFT LCD)
100 ECGs in internal memory




SE-601A
50 ECGs in internal memory




SE-601B
Vivid waveform display on large screen
(5.7 inch STN LCD)
100 ECGs in internal memory

- Portable, lightweight design**
Convenient for mobile use and offices with limited space
- Easy data input and operation**
Alphanumeric keyboard and one-touch operation
- Power supply**
Built-in rechargeable battery, AC/DC power supply
- Pacemaker detection**
Pacemaker detection which meets the requirements of ANSI/AAMI ECI1
- Interpretation**
Automatic measurement and interpretation for adults and pediatrics
- Periodic recording**
Two-step exercise test with periodic recording
- HRV analysis**
Heart rate variability (HRV) analysis
- Recording**
Internal thermal printer and external printer
- Memory and data transmission**
Support external archiving: SD card and card reader, flash disk
Data transmission to PC via Ethernet or RS232 port

- Options**
Internal storage upgrade to 200 ECGs
PC-based data management software (Smart ECG Viewer)
XML format export
SD card and card reader, flash disk
Rolling stand and Carrying bag




12 lead ECG waveform
Rich print formats for different needs



Interpretation
Automatic measurement and interpretation tested with authoritative CSE database



Rhythm recording
Single lead or three leads selectable



HRV analysis report
Heart rate variability (HRV) analysis